



ROG STRIX XG27UCG

USER GUIDE

3.2 Specifications summary

Panel type	TFT LCD 27"W (68.5 cm) wide screen 3840 x
Panel size	2160 0.155 mm x 0.155 mm 350 cd/m2; 400
Max. resolution	cd/m2 (HDR peak) 1000:1
Pixel pitch	178"/178°
Brightness (Typ.)	1.07 B
Contrast ratio (Typ.)	1ms (GTG)
Viewing angle(H/V) CR>10	8 color temperatures
Display colors	No
Response time	DisplayPort v1.4 x 1, HDMI v2.1 x 1, USB
Color temperature selection	Type-C
Analog input	x 1
Digital input	Yes
Earphone jack	No
Audio input	Black/White
Speaker (Built-in)	White (On)/Amber (Standby)
Colors	+20° ~ -5°
Power LED	+/-90°
Tilt	+45° ~ -45°
Pivot	120 mm
Swivel	100 x 100 mm
Height adjustment	Yes
VESA wall mount	AC: 100~240V, 50~60Hz, 1.5 A
Kensington lock	DC: 20 V, 6 A (AC adapter)
Voltage rating	Power On: < 30 W**, Standby: < 0.5 W, Power
Power consumption	Off: < 0.3 W
Temperature (Operating)	0°C~40°C -20°C~+60°C 61.37 x 36.72 x 8.98
Temperature (Non-operating)	cm (without stand)
Dimensions (W x H x D)	61.37 x 38.96 x 21.88 cm (with stand, lowest)
Weight (Esti.)	61.37 x 50.96 x 21.88 cm (with stand, highest)
Multi-languages	71.9 x 24.0 x 46.0 cm (package)
	3.8 kg (without stand); 6.6 kg (Net); 9.1 kg
	(Gross)
	23 languages (English, French, German,
	Italian, Spanish, Dutch, Portuguese, Russian,
	Czech, Croatian, Polish, Romanian,
	Hungarian,
	Turkish, Simplified Chinese, Traditional
	Chinese,
	Japanese, Korean, Thai, Indonesian, Persian,
	Ukrainian, Vietnamese)

Accessories	Quick start guide, warranty card, power adapter, power cord, DP cable, ROG sticker, ROG pouch
Compliance and standards	cTUVus, FCC, ICES-3, CB, CE, ErP, WEEE, UkrSEPRO, Ukraine Energy Label, CU(EAC LOGO), CCC, China Energy Label, BSMI, RCM, VCCI, PC Recycle, J-MOSS, KCC, KMEPS, RoHs, CEC, HDMI, DP, DisplayHDR 400, VESA Adaptive Sync, WHQL Windows 10/11, TUV Flicker free, TUV Low Blue Light, EU Energy label

***Specifications are subject to change without notice.**

****Measuring a screen brightness of 200 nits without audio/USB/Card reader connection.**