



DELL P Series P2424HT monitor de computadora 60.5 cm (23.8") 1920 x 1080 Pixeles Full HD LCD Pantalla táctil Negro, Plata

Marca : DELL

Familia de productos: P
Series

Código del producto:
P2424HT

Nombre del producto :
P2424HT



- 60.5cm (23.8") Full HD 1920 x 1080 LED IPS
- 8ms, 16:9, 300cd/m², 1000:1
- USB, HDMI, DisplayPort

60.5cm (23.8") Full HD 1920 x 1080 LED IPS, 16:9, 300cd/m², 16.78M, 8ms, 178°/178°, 1000:1

DELL P Series P2424HT. Diagonal de la pantalla: 60.5 cm (23.8"), Resolución de la pantalla: 1920 x 1080 Pixeles, Tipo HD: Full HD, Tecnología de visualización: LCD, Tiempo de respuesta: 8 ms, Relación de aspecto nativa: 16:9, Ángulo de visión, horizontal: 178°, Ángulo de visión, vertical: 178°. Altavoces incorporados. Concentrador USB integrado. montaje VESA, Ajustes de altura. Color del producto: Negro, Plata



Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Tilt adjustment	✓
Display resolution *	1920 x 1080 pixels	Tilt angle range	-5 - 60°
HD type *	Full HD	On Screen Display (OSD)	✓
Native aspect ratio *	16:9	Plug and Play	✓
Display technology *	LCD	LED indicators	✓
Panel type *	IPS		
Backlight type	LED	Power	
Touchscreen *	✓	Energy efficiency class (SDR) *	E
Display brightness (typical)	300 cd/m² 8 ms	Energy efficiency class (HDR) *	Not available
Response time *	✓	Energy consumption (SDR) per 1000 hours *	18 W
Anti-glare screen	Flat 480p, 576p, 720p,	Power consumption (typical) *	0.5 W
Screen shape *	1080i, 1080p 1000:1 60 Hz	Power consumption (standby) *	190 W
Supported video modes	178° 178° 16.78 million	Power consumption (max)	0.3 W
Contrast ratio (typical) *	colours 5 ms 0.2745 x	Power consumption (off)	100 - 240 V
Maximum refresh rate *	0.2745 mm 93 ppi 30 - 88	AC input voltage	50/60 Hz
Viewing angle, horizontal	kHz 48 - 75 Hz 52.7 cm 29.6	AC input frequency	Internal
Viewing angle, vertical	cm 60.5 cm 60.47 cm 3H 6	Power supply type	A to G
Display number of colours *	bit	Energy efficiency scale	1465328
Response time (fast)		European Product Registry for	
Pixel pitch		Energy Labelling (EPREL) code	
Pixel density		Operational conditions	
Horizontal scan range		Operating temperature (T-T)	0 - 40 °C
Vertical scan range		Storage temperature (T-T)	-20 - 60 °C
Viewable size, horizontal		Operating relative humidity (H-H)	10 - 80%
Viewable size, vertical		Storage relative humidity (H-H)	5 - 90%
Viewable size diagonal		Operating altitude	0 - 5000 m
Display diagonal (metric)		Non-operating altitude	5000 - 12192 m
Surface hardness			
Colour depth			

Display		Weight & dimensions	
sRGB coverage (typical)	99%	Width (with stand)	538.8 mm
Performance		Depth (with stand)	248.9 mm
Low Blue Light technology	✓	Height (with stand)	431.5 mm
Multimedia		Weight (with stand)	7.86 kg
RMS rated power	3	Width (without stand)	538.8 mm
Built-in speaker(s) *	W	Depth (without stand)	54.1 mm
Built-in camera *	✓	Height (without stand)	321 mm
Design		Weight (without stand)	3.86 kg
Market positioning *	Business	Bezel width (side)	5.88 mm
Product colour *	Black, Silver	Bezel width (top)	5.87 mm
Front bezel colour	Black	Bezel width (bottom)	1.86 cm
Feet colour	Silver	Packaging data	
Ports & interfaces		Package weight	10.8 kg
Built-in USB hub * USB	✓	Packaging content	
upstream port type	USB Type-C	Stand included	✓
Number of USB Type-C	1	Cables included	AC, DisplayPort, USB Type-A to USB Type-C, USB Type-C to USB Type-C
upstream ports quantity	2	Quick start guide	✓
USB Type-A downstream ports quantity	1	DisplayPort cable length	1.8 m
USB Type-C downstream ports quantity	✓	Sustainability	
USB Type-C DisplayPort	✓	Sustainability compliance	✓
Alternate Mode	90 W	Sustainability certificates	ENERGY STAR
USB Power Delivery (USB PD)	✓	Doesn't contain	PVC/BFR
USB Power Delivery up to	1	Carbon footprint	
HDMI *	1.4	Total carbon footprint (kg of CO2e)	333
HDMI ports quantity	1	Total carbon emissions, standard deviation (kg of CO2e)	149
HDMI version	1.2	Carbon emissions, manufacturing (kg of CO2e)	397
DisplayPorts quantity	✓	Carbon emissions, logistics (kg of CO2e)	53
DisplayPort version	3.5 mm	Carbon emissions, energy usage (kg of CO2e)	197
Headphone out *	✓	Carbon emissions, end-of-life (kg of CO2e)	6
Headphone connectivity	✓	Total carbon emissions, w/o use phase (kg of CO2e)	456
HDCP	1.4	PAIA version	1.3.2
Ergonomics		Other features	
VESA mounting *	✓	RJ-45 ports quantity	1
Panel mounting interface	100 x 100 mm	Heavy metals free	Hg (mercury)
Cable management	✓	Compliance certificates	RoHS
Cable lock slot *	✓		
Cable lock slot type	Kensington		
Height adjustment *	✓		
Adjustable height (max)	11.1 cm		
Swivelling	✓		
Swivel angle range	-30 - 30°		