

FEATURE	TECHNICAL SPECIFICATION
MODEL	Dell 24 Monitor - P2425H
DIAGONAL VIEWING SIZE	60.47 cm (23.8")
PRESET DISPLAY AREA (H X V)	527.04 mm x 296.46 mm (20.75" x 11.67")
PANEL TYPE	In-Plane Switching (IPS) technology
DISPLAY SCREEN COATING	Anti-glare with 3H hardness
MAXIMUM PRESET RESOLUTION	1920 x 1080
REFRESH RATE	Up to 100 Hz
VIEWING ANGLE	178° vertical / 178° horizontal
PIXEL PITCH	0.2745 mm x 0.2745 mm
PIXEL PER INCH (PPI)	92.53
CONTRAST RATIO	1,500: 1 (typical)
ASPECT RATIO	16:9
BACKLIGHT TECHNOLOGY	LED edgelight system
BRIGHTNESS	250 cd/m2 (typical)
RESPONSE TIME	5ms gray-to-gray (Fast mode) 8ms gray-to-gray (Normal mode)
COLOR SUPPORT	Color Gamut: 99% sRGB Color Depth: Up to 16.7 million colors Yes, 4-Star
TÜV EYE COMFORT	Yes
FLICKER FREE	Yes
CONNECTIVITY	• 1 x HDMI 1.4 (HDCP 1.4) (Supports up to FHD 1920 x 1080 100Hz TMDS as per specified in HDMI 1.4) • 1 x DP 1.2 (HDCP 1.4) • 1 x VGA • 1 x USB 3.2 Gen1 Type-B upstream • 3 x USB 3.2 Gen1 Type-A downstream • 1 x USB 3.2 Gen1 Type-C downstream with up to 15W PD (data only)
USB POWER DELIVERY	Yes, up to 15W via USB-C downstream port
ADJUSTABILITY	Height: Up to 150 mm (5.9") Tilt: -5° ~ 21° Swivel: -45° ~ 45° Pivot: -90° ~ 90°
DELL DISPLAY MANAGER COMPATIBILITY	Yes with Easy Arrange
REMOTE ASSET MANAGEMENT	Yes
SPECIFICATIONS - SERVICE / SUPPORT DETAILS	3 Year Limited Hardware Warranty with Advanced Exchange Service and Premium Panel Exchange

FEATURE	TECHNICAL SPECIFICATION
VOLTAGE REQUIRED	100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 1.5 A (typ)
ENERGY EFFICIENCY CLASS (A TO G SCALE)	C 
POWER CONSUMPTION (OPERATIONAL) (TYPICAL)	0.3 W (Off mode) 0.3 W (Standby mode) 11.7 W (On mode) 65 W (Max) 12.0 W (Pon) 38.4 kWh (TEC)
AUDIO OUTPUT	Optional soundbar (sold separately)
HEIGHT WITH STAND (COMPRESSED ~ EXTENDED)	364.00 mm ~ 496.53 mm (14.33" ~ 19.55")
WIDTH WITH STAND	538.64 mm (21.21")
DEPTH WITH STAND	181.75 mm (7.16")
HEIGHT WITHOUT STAND	314.23 mm (12.37")
WIDTH WITHOUT STAND	538.64 mm (21.21")
DEPTH WITHOUT STAND	50.03 mm (1.97")
WEIGHT (PANEL ONLY - FOR VESA MOUNT)	3.12 kg (6.88 lbs)
WEIGHT (WITH PACKAGING)	6.78 kg (14.95 lbs)
SECURITY	Security-lock slot (based on Kensington Security Slot™)
COMPLIANT STANDARDS	• ENERGY STAR® certified monitor • EPEAT® GOLD • EPEAT® Climate+ • TCO Certified Displays • TCO Certified Edge • RoHS-compliant • BFR / PVC free monitor (excluding external cables) • Arsenic-free glass and mercury-free (panel only)
FLAT PANEL MOUNT INTERFACE	VESA (100 mm x 100mm)
TEMPERATURE RANGE	Operating: 0°C ~ 40°C (32°F ~ 104°F) Non-operating: -20° ~ 60°C (-4° ~ 140°F)
HUMIDITY RANGE	Operating: 10% ~ 80% (non-condensing) Non-operating: 5% ~ 90% (non-condensing)
ALTITUDE	Operating: 5,000 m (16,404 ft) max Non-operating: 12,192 m (40,000 ft) max
WHAT'S INCLUDED	1 x Monitor panel 1 x Stand riser and base 1 x Power cord 1 x DP-to-DP cable, 1.8m 1 x USB 3.2 Gen1 Type A-to-B (upstream) cable, 1.8m 1 x Quick setup guide 1 x Safety, Environmental, and Regulatory Information

FEATURE	TECHNICAL SPECIFICATION
MODEL	Dell 24 Monitor - P2425H without stand ¹
DIAGONAL VIEWING SIZE	60.47 cm (23.8")
PRESET DISPLAY AREA (H X V)	527.04 mm x 296.46 mm (20.75" x 11.67")
PANEL TYPE	In-Plane Switching (IPS) technology
DISPLAY SCREEN COATING	Anti-glare with 3H hardness
MAXIMUM PRESET RESOLUTION	1920 x 1080
REFRESH RATE	Up to 100 Hz
VIEWING ANGLE	178° vertical / 178° horizontal
PIXEL PITCH	0.2745 mm x 0.2745 mm
PIXEL PER INCH (PPI)	92.53
CONTRAST RATIO	1,500: 1 (typical)
ASPECT RATIO	16:9
BACKLIGHT TECHNOLOGY	LED edgelight system
BRIGHTNESS	250 cd/m2 (typical)
RESPONSE TIME	5ms gray-to-gray (Fast mode) 8ms gray-to-gray (Normal mode)
COLOR SUPPORT	Color Gamut: 99% sRGB Color Depth: Up to 16.7 million colors
TÜV EYE COMFORT	Yes, 4-Star
FLICKER FREE	Yes
CONNECTIVITY	• 1 x HDMI 1.4 (HDCP 1.4) (Supports up to FHD 1920 x 1080 100Hz TMDS as per specified in HDMI 1.4) • 1 x DP 1.2 (HDCP 1.4) • 1 x VGA • 1 x USB 3.2 Gen1 Type-B upstream • 3 x USB 3.2 Gen1 Type-A downstream • 1 x USB 3.2 Gen1 Type-C downstream with up to 15W PD (data only)
USB POWER DELIVERY	Yes, up to 15W via USB-C downstream port
DELL DISPLAY MANAGER COMPATIBILITY	Yes with Easy Arrange
REMOTE ASSET MANAGEMENT	Yes
SPECIFICATIONS - SERVICE / SUPPORT DETAILS	3 Year Limited Hardware Warranty with Advanced Exchange Service and Premium Panel Exchange

FEATURE	TECHNICAL SPECIFICATION
VOLTAGE REQUIRED	100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 1.5 A (typ)
ENERGY EFFICIENCY CLASS (A TO G SCALE)	C 
POWER CONSUMPTION (OPERATIONAL) (TYPICAL)	0.3 W (Off mode) 0.3 W (Standby mode) 11.7 W (On mode) 65 W (Max) 12.0 W (Pon) 38.4 kWh (TEC)
AUDIO OUTPUT	Optional soundbar (sold separately)
HEIGHT WITHOUT STAND	314.23 mm (12.37")
WIDTH WITHOUT STAND	538.64 mm (21.21")
DEPTH WITHOUT STAND	50.03 mm (1.97")
WEIGHT (PANEL ONLY - FOR VESA MOUNT)	3.12 kg (6.88 lbs)
WEIGHT (WITH PACKAGING)	5.34 kg (11.77 lbs)
SECURITY	Security-lock slot (based on Kensington Security Slot™)
COMPLIANT STANDARDS	• ENERGY STAR® certified monitor • EPEAT® GOLD • EPEAT® Climate+ • TCO Certified Displays • TCO Certified Edge • RoHS-compliant • BFR / PVC free monitor (excluding external cables) • Arsenic-free glass and mercury-free (panel only)
FLAT PANEL MOUNT INTERFACE	VESA (100 mm x 100mm)
TEMPERATURE RANGE	Operating: 0°C ~ 40°C (32°F ~ 104°F) Non-operating: -20° ~ 60°C (-4° ~ 140°F)
HUMIDITY RANGE	Operating: 10% ~ 80% (non-condensing) Non-operating: 5% ~ 90% (non-condensing)
ALTITUDE	Operating: 5,000 m (16,404 ft) max Non-operating: 12,192 m (40,000 ft) max
WHAT'S INCLUDED	1 x Monitor panel 1 x Power cord 1 x DP-to-DP cable, 1.8m 1 x USB 3.2 Gen1 Type A-to-B (upstream) cable, 1.8m 1 x Quick setup guide 1 x Safety, Environmental, and Regulatory Information