

FEATURE	TECHNICAL SPECIFICATION
MODEL	Dell 32 Plus 4K Monitor - S3225QS
DIAGONAL VIEWING SIZE	800.1 mm (31.5 in.)
PANEL TYPE	Vertical Alignment (VA) Technology
MAXIMUM PRESET RESOLUTION AND REFRESH RATE	3840 x 2160 up to 120 Hz
VIEWING ANGLE	Horizontal: 178° Vertical: 178°
PIXEL PITCH	Horizontal: 0.18159 mm Vertical: 0.18159 mm
PIXEL PER INCH (PPI)	139
CONTRAST RATIO	3000:1 (typical)
ASPECT RATIO	16:9
BACKLIGHT TECHNOLOGY	LED Edgelight System
BRIGHTNESS	300 cd/m ² (typical)
HDR	HDR10
RESPONSE TIME	•Normal mode: 8 ms (gray to gray) •Fast mode: 5 ms (gray to gray) •Extreme mode: 4 ms (gray to gray)
COLOR GAMUT	•sRGB 99% (CIE 1931) (typical) •DCI-P3 95% (CIE 1976) (typical)
COLOR DEPTH	1.07 billion colors
TÜV EYECOMFORT	4 star
CONNECTIVITY	Video port •2 x HDMI ports (HDCP 1.4 and 2.2) (Supports up to UHD 3840 x 2160, 120 Hz, FRL, HDR, VRR as per specified in HDMI 2.1) •1 x DisplayPort 1.4 (HDCP 1.4 and 2.2) (Supports up to UHD 3840 x 2160, 120 Hz, HDR, VRR) USB port •Not Applicable
VARIABLE REFRESH RATE	•AMD FreeSync™ Premium •HDMI VRR
ADJUSTABILITY	Height adjustment up to 100 mm Tilt -5°/+21° Swivel: Not Applicable Slant adjust -4°/+4° Anti-glare with hard-coating 3H
DISPLAY SCREEN COATING	
SOFTWARE COMPATIBILITY	Dell Display and Peripheral Manager (DDPM) for Windows operating system
REMOTE ASSET MANAGEMENT	Yes, using Dell Display and Peripheral Manager
VOLTAGE REQUIRED	100 VAC to 240 VAC/50 Hz or 60 Hz ± 3 Hz/1.5 A
POWER CONSUMPTION	0.3 W (Off mode) 0.3 W (Standby mode) 32.0 W (On mode) 85 W (Maximum) 31.0 W (Pon) 96.8 kWh (TEC)
AUDIO OUTPUT	2 Integrated 5 W speakers

FEATURE	TECHNICAL SPECIFICATION
BEZEL WIDTH – TOP	7.62 mm (0.30 in.) 7.62 mm (0.30 in.)
BEZEL WIDTH – LEFT OR RIGHT	
BEZEL WIDTH – BOTTOM	13.00 mm (0.51 in.)
DIMENSIONS (WITH STAND) – HEIGHT (EXTENDED)	545.74 mm (21.49 in.)
DIMENSIONS (WITH STAND) – HEIGHT (COMPRESSED)	445.74 mm (17.55 in.)
DIMENSIONS (WITH STAND) – WIDTH	712.54 mm (28.05 in.)
DIMENSIONS (WITH STAND) – DEPTH	221.84 mm (8.73 in.)
DIMENSIONS (WITHOUT STAND) – HEIGHT	412.77 mm (16.25 in.)
DIMENSIONS (WITHOUT STAND) – WIDTH	712.54 mm (28.05 in.)
DIMENSIONS (WITHOUT STAND) – DEPTH	61.36 mm (2.42 in.)
STAND DIMENSIONS – HEIGHT (EXTENDED)	410.30 mm (16.15 in.)
STAND DIMENSIONS – HEIGHT (COMPRESSED)	371.91 mm (14.64 in.)
STAND DIMENSIONS – WIDTH	259.01 mm (10.20 in.)
STAND DIMENSIONS – DEPTH	221.84 mm (8.73 in.)
WEIGHT WITH PACKAGING	13.65 kg (30.09 lb)
WEIGHT WITH STAND ASSEMBLY AND CABLES	8.77 kg (19.33 lb)
WEIGHT WITHOUT STAND ASSEMBLY (WITHOUT CABLES)	5.97 kg (13.16 lb)
WEIGHT OF STAND ASSEMBLY	2.53 kg (5.58 lb)
FLAT PANEL MOUNT INTERFACE	VESA (100 mm x 100 mm)
SECURITY	Security lock slot (cable lock sold separately)
COMPLIANT STANDARDS	•ENERGY STAR 8.0 •RoHS Compliant •Product Safety, EMC and Environmental Datasheets •Dell Regulatory Compliance Home Page •Dell and the Environment •TÜV Eye Comfort 4 Star •BFR/PVC reduce monitor (Circuit boards are made from BFR/PVC-free laminates.). •Arsenic-Free glass and Mercury-Free for the panel only.

FEATURE	TECHNICAL SPECIFICATION
TEMPERATURE RANGE	<ul style="list-style-type: none"> •Operating: 0°C to 40°C (32°F to 104°F) •Non-Operating: -20°C to 60°C (-4°F to 140°F)
HUMIDITY RANGE	<ul style="list-style-type: none"> •Operating: 10% to 80% (non-condensing) •Non-Operating: 5% to 90% (non-condensing) •Operating: 5,000 m (16,400 ft) maximum
ALTITUDE	<ul style="list-style-type: none"> •Non-Operating: 12,191 m (40,000 ft) maximum
WHAT'S INCLUDED	<ul style="list-style-type: none"> • Monitor •Side I/O-Cover •Stand riser •Stand base •Power cable •1 x HDMI cable - 1.80 m •QR card •Safety, Environmental, and Regulatory Information •(US/Canada) 1-year Advanced Exchange Service¹ and
STANDARD SERVICE PLAN	<ul style="list-style-type: none"> • Premium Panel Exchange •(WW) 3-year Advanced Exchange Service¹ and Premium Panel Exchange