



Made to be seen. And heard.

—

Dell 24 Monitor | S2425H
Dell 27 Monitor | S2725H

The world's # 1 monitor company*

FEATURE	TECHNICAL SPECIFICATION	TECHNICAL SPECIFICATION
MODEL	Dell 24 Monitor – S2425H	Dell 27 Monitor – S2725H
DIAGONAL VIEWING SIZE	60.47 cm 23.8 Inches	68.60 cm 27 Inches
PRESET DISPLAY AREA (H X V)	527.04 mm x 296.46 mm 20.75" x 11.67" In-Plane Switching (IPS) technology	597.89 mm x 336.31 mm 23.54" x 13.24" In-Plane Switching (IPS) technology
PANEL TYPE	Antiglare with hard-coating 3H	Antiglare with hard-coating 3H
DISPLAY SCREEN COATING		
MAXIMUM PRESET RESOLUTION	1920 x 1080	1920 x 1080
REFRESH RATE	100 Hz	100 Hz
VIEWING ANGLE	(178° vertical / 178° horizontal)	(178° vertical / 178° horizontal)
PIXEL PITCH	0.2745 mm x 0.2745 mm	0.3114 mm x 0.3114 mm
PIXEL PER INCH (PPI)	93	82
CONTRAST RATIO	1500: 1 (typical)	1500: 1 (typical)
ASPECT RATIO	16:9	16:9
BACKLIGHT TECHNOLOGY	LED edgelight system	LED edgelight system
BRIGHTNESS	250 cd/m2 (typical)	300 cd/m2 (typical)
RESPONSE TIME	8 ms (Normal mode) 5 ms (Fast mode) 4 ms (Extreme mode1)	8 ms (Normal mode) 5 ms (Fast mode) 4 ms (Extreme mode1)
COLOR SUPPORT	Color Gamut (typical): 99% sRGB (typical) (CIE1931) Color Depth: 16.7 million colors	Color Gamut (typical): 99% sRGB (typical) (CIE1931) Color Depth: 16.7 million colors
TÜV EYE COMFORT	Yes, 4 Star	Yes, 4 Star
FLICKER FREE	Yes	Yes
CONNECTIVITY	2 x HDMI (HDCP1.4) (Supports up to FHD 1920 x 1080 100Hz, as per specified in HDMI1.4) Tilt -5° to 21°	2 x HDMI (HDCP1.4) (Supports up to FHD 1920 x 1080 100Hz, as per specified in HDMI1.4) Tilt -5° to 21°
ADJUSTABILITY	No	No
DAISY CHAIN AVAILABILITY		
DELL DISPLAY MANAGER COMPATIBILITY	Yes with Easy Arrange2	Yes with Easy Arrange2
VOLTAGE REQUIRED	100 VAC to 240 VAC/50 Hz or 60 Hz ± 3 Hz/1.5 A	100 VAC to 240 VAC/50 Hz or 60 Hz ± 3 Hz/1.5 A
POWER CONSUMPTION	0.3 W (Off Mode)3 0.4 W (Standby Mode)3 14.5 W (On Mode)3 42 W (Max)4 13.0 W (Pon)5 41.1 kWh (TEC)5	0.3 W (Off Mode)3 0.4 W (Standby Mode)3 17.0 W (On Mode)3 45 W (Max)4 15.0 W (Pon)5 47.0 kWh (TEC)5
AUDIO OUTPUT	Integrated 2 x 5W speakers	Integrated 2 x 5W speakers
HEIGHT WITH STAND (COMPRESSED ~ EXTENDED)	411.73 mm (16.21 in.)	452.21 mm (17.80 in.)
WIDTH WITH STAND	537.64 mm (21.17 in.)	609.69 mm (24.00 in.)
DEPTH WITH STAND	163.00 mm (6.42 in.)	176.50 mm (6.95 in.)
HEIGHT WITHOUT STAND	313.73 mm (12.35 in.)	354.21 mm (13.95 in.)

1 Reduced visible motion blur and increased image responsiveness. NOTE: Using Extreme mode might introduce minor and noticeable visual artifacts in the image. You can choose Normal or Fast mode to mitigate these visual artifacts.

2 Requires Dell Display Manager software installation.

3 As defined in EU 2019/2021 and EU 2019/2013.

4 Max brightness and contrast setting with maximum power loading on all USB ports.

5 Pon: Power consumption of On mode as defined in Energy Star 8.0 version. TEC: Total energy consumption in kWh as defined in Energy Star 8.0 version.

FEATURE	TECHNICAL SPECIFICATION	TECHNICAL SPECIFICATION
MODEL	Dell 24 Monitor – S2425H	Dell 27 Monitor – S2725H
WIDTH WITHOUT STAND	537.64 mm (21.17 in.)	609.69 mm (24.00 in.)
DEPTH WITHOUT STAND	58.81 mm (2.32 in.)	59.04 mm (2.32 in.)
WEIGHT (PANEL ONLY - FOR VESA MOUNT)	3.29 kg (7.25 lb)	4.30 kg (9.48 lb)
WEIGHT (WITH PACKAGING)	5.92 kg (13.05 lb)	7.31 kg (16.11 lb)
SECURITY	Security-lock slot (for Kensington locks, sold separately)	Security-lock slot (for Kensington locks, sold separately)
COMPLIANT STANDARDS	<ul style="list-style-type: none"> • RoHS-compliant • BFR/PVC reduce monitor (The circuit boards are made from BFR/PVC-free laminates.) • Arsenic-free glass and Mercury-free for the panel only • ENERGY STAR® certified monitor 	<ul style="list-style-type: none"> • RoHS-compliant • BFR/PVC reduce monitor (The circuit boards are made from BFR/PVC-free laminates.) • Arsenic-free glass and Mercury-free for the panel only • ENERGY STAR® certified monitor
FLAT PANEL MOUNT INTERFACE	VESA (100 mm)	VESA (100 mm)
TEMPERATURE RANGE	Operating: 0° to 40°C (32° to 104°F) Non-operating: -20° to 60° (-4° to 140° F)	Operating: 0° to 40°C (32° to 104°F) Non-operating: -20° to 60° (-4° to 140° F)
HUMIDITY RANGE	Operating: 10% to 80% (non-condensing) Non-Operating: 5% to 90% (non-condensing) Operating: 5,000 m (16,400 ft) max	Operating: 10% to 80% (non-condensing) Non-Operating: 5% to 90% (non-condensing) Operating: 5,000 m (16,400 ft) max
ALTITUDE	Non-Operating: 12,192 m (40,000 ft) max • Monitor	Non-Operating: 12,192 m (40,000 ft) max • Monitor
WHAT'S INCLUDED	<ul style="list-style-type: none"> • Stand riser and base • Side I/O Cover • VESA cover • Power cable • 1 x HDMI cable • Quick setup guide • Safety, Environmental, and Regulatory Information (US/Canada) 1-year Advanced Exchange Service1 & Premium Panel	<ul style="list-style-type: none"> • Stand riser and base • Side I/O Cover • VESA cover • Power cable • 1 x HDMI cable • Quick setup guide • Safety, Environmental, and Regulatory Information (US/Canada) 1-year Advanced Exchange Service1 & Premium Panel
STANDARD SERVICE PLAN	Exchange (WW) 3-year Advanced Exchange Service1 & Premium Panel Exchange	Exchange (WW) 3-year Advanced Exchange Service1 & Premium Panel Exchange

¹ Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.

Technical specifications subject to change without prior notice. Product availability varies by country. Please contact your Dell representative for more information.

© 2024 Dell Inc. or its subsidiaries. All Rights Reserved. Dell Technologies, Dell, EMC, Dell EMC and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum. Thunderbolt and the Thunderbolt logo are trademarks of Intel Corporation in the U.S. and/or other countries.