

FEATURE	TECHNICAL SPECIFICATION
MODEL	Dell UltraSharp 27 Monitor - U2724D
DIAGONAL VIEWING SIZE	684.70 mm (27.00 inches)
PRESET DISPLAY AREA (H X V)	596.74 mm x 335.66 mm (23.49" x 13.22")
PANEL TYPE	IPS Black Technology
DISPLAY SCREEN COATING	Anti-Glare with 3H hardness
MAXIMUM PRESET RESOLUTION	2560 x 1440 at 120 Hz
VIEWING ANGLE	178° vertical / 178° horizontal
PIXEL PITCH	0.2331 mm x 0.2331 mm
PIXEL PER INCH (PPI)	108.97
CONTRAST RATIO	2000 to 1 (typical)
ASPECT RATIO	16:9
BACKLIGHT TECHNOLOGY	LED
BRIGHTNESS	350 cd/m2 (typical)
RESPONSE TIME	8 ms (Normal) 5 ms (Fast)
AMBIENT LIGHT SENSOR	Yes, auto brightness and color temperature adjustment
TÜV EYE COMFORT CERTIFICATION	5 Stars
CONNECTIVITY	<ul style="list-style-type: none"> • 1 x DP 1.4 (DRR for Microsoft Windows) (Supports 2 x QHD 120Hz 8 bit) • 1 x DP out • 1 x HDMI (HDCP 1.4)(Supports up to QHD 2560 x 1440 120Hz TMDS, VRR as per specified in HDMI 2.1) • 1 x USB-C upstream (Data only, USB 3.2 Gen 2, 10Gbps) • 2 x USB-A (USB 3.2 Gen 2 10Gbps) • 1 x audio lineout Quick Access: <ul style="list-style-type: none"> • 1 x USB-A (USB 3.2 Gen 2 10Gbps with BC 1.2) • 1 x USB-C downstream (USB 3.2 Gen 2 10Gbps, 15 W)
ADJUSTABILITY	Height adjustable (150 mm) Tilt (-5° to 21°) Swivel (-45° to 45°) Pivot (-90° to 90°)
PBP / PIP	Yes
KEYBOARD, VIDEO AND MOUSE (KVM)	No
DAISY CHAIN AVAILABILITY	Yes
AUDIO OUTPUT	1 x Audio line-out1
BUILT-IN SPEAKER	No
DELL DISPLAY MANAGER COMPATIBILITY	Yes, Easy Arrange, Other key features

FEATURE	TECHNICAL SPECIFICATION
SPECIFICATIONS - SERVICE / SUPPORT DETAILS	3-Year Advanced Exchange Service and Premium Panel Exchange
COLOR GAMUT	<ul style="list-style-type: none"> • 100% sRGB • 100% BT.709 • 98% Display P3 • 98% DCI-P3 • 1.07 billion colors • Delta E < 2 (average) (sRGB, BT.709, Display P3, DCI-P3)
HEIGHT WITH STAND (COMPRESSED ~ EXTENDED)	385.58 mm ~ 535.58 mm (15.18" ~ 21.09")
WIDTH WITH STAND	612.24 mm (24.10")
DEPTH WITH STAND	192.28 mm (7.57")
HEIGHT WITHOUT STAND	352.51 mm (13.88")
WIDTH WITHOUT STAND	612.24 mm (24.10")
DEPTH WITHOUT STAND	50.12 mm (1.97")
WEIGHT (PANEL ONLY - FOR VESA MOUNT)	4.49 kg (9.90 lb)
WEIGHT (WITH STAND ASSEMBLY AND CABLES)	6.56 kg (14.46 lb)
WEIGHT (WITH PACKAGING)	9.40 kg (20.72 lb)
SECURITY	Security lock slot (cable lock sold separately) Anti-theft stand lock slot (to lock stand to monitor using screw)
COMPLIANT STANDARDS	<ul style="list-style-type: none"> • ENERGY STAR® certified monitor • EPEAT® registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration status by country. • TCO Certified & TCO Certified Edge • RoHS Compliant • BFR/PVC Free monitor (excluding external cables). • Arsenic-Free glass and Mercury-Free for the panel only
FLAT PANEL MOUNT INTERFACE	VESA mounting holes (100 mm x 100 mm - behind attached VESA Cover)
TEMPERATURE RANGE	Operating: 0°C to 40°C (32°F to 104°F) Non-operating: -20°C to 60°C (-4°F to 140°F) Operating: 10% to 80% (non-condensing)
HUMIDITY RANGE	Non-Operating: 5% to 90% (non-condensing) Operating: 5000 m (16404 ft) max
ALTITUDE	Non-Operating: 12192 (40000 ft) max 100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 1.6 A (typical)
VOLTAGE REQUIRED	0.3 W (Off mode)2 0.5 W (Standby mode)2 23.9 W (On mode)2
POWER CONSUMPTION NORMAL OPERATION	85 W (Max.)3 17.1 W (Pon)4 54.4 kWh (TEC)4 Monitor, Stand Riser, Stand Base
WHAT'S INCLUDED	1 x Power cable 1 x DP Cable (DP to DP) - 1.8 m 1 x USB-A to USB-C Gen 2 cable - 1 m Quick setup guide Safety, Environmental and Regulatory Information Factory calibration report

1 Headphone usage is not supported for the audio line out connector.

2 As defined in EU 2019/2021 and EU 2019/2013.

3 Max brightness and contrast setting with maximum power loading on all USB ports.

4 Pon: Power consumption of On Mode as defined in Energy Star 8.0. TEC: Total energy consumption in kWh as defined in Energy Star 8.0 version.