

FEATURE MODEL	TECHNICAL SPECIFICATION
	Dell UltraSharp 40 Curved Thunderbolt™ Hub Monitor - U4025QW
DIAGONAL VIEWING SIZE	1008.59 mm (39.7 inches)
PRESET DISPLAY AREA (H X V)	929.28 mm x 392.04 mm (36.59 inches x 15.43 inches)
PANEL TYPE	IPS Black Technology
DISPLAY SCREEN COATING	Anti-Glare with 3H hardness
MAXIMUM PRESET RESOLUTION	5120 x 2160 at 120 Hz
VIEWING ANGLE	178° vertical / 178° horizontal
PIXEL PITCH	0.1815 mm x 0.1815 mm
PIXEL PER INCH (PPI)	140
CONTRAST RATIO	2000 to 1 (typical)
CURVATURE	2500R
ASPECT RATIO	21:9
BACKLIGHT TECHNOLOGY	LED Edgelight System
BRIGHTNESS	450 cd/m² (typical) 600 cd/m² (HDR Peak)
RESPONSE TIME	8 ms (Normal mode) 5 ms (Fast mode) Yes, VESA DisplayHDR600
HDR READY	Yes, auto brightness and color temperature adjustment
AMBIENT LIGHT SENSOR	
TÜV EYE COMFORT CERTIFICATION	5 Stars
CONNECTIVITY	<ul style="list-style-type: none"> <li>1 x HDMI (supports up to 5K2K 5120 x 2160 120Hz FRL, HDR Static Metadata, VRR as per specified in HDMI 2.1.)</li> <li>1 x DP 1.4 (HDCP 2.3) (Support up to 5120 x 2160 120Hz, HDR, DSC)</li> <li>1 x Thunderbolt™ 4 downstream port (15W) for daisy chaining (Video + Data)</li> <li>1 x Thunderbolt™ 4 (140W) (Alternate mode with DisplayPort 1.4, SuperSpeed USB 3.2 Gen2 (10Gbps) upstream port, USB Power Delivery up to 140W)</li> <li>1 x USB Type-C® upstream port (data only) (SuperSpeed USB 10Gbps, USB 3.2 Gen2)</li> <li>4 x USB Type-A downstream port (SuperSpeed USB 10Gbps, USB 3.2 Gen2)</li> <li>1 x Audio line-out</li> <li>1 x RJ45 (2.5GbE)</li> </ul> <p>Quick Access:</p> <ul style="list-style-type: none"> <li>1 x USB Type-A downstream port (SuperSpeed USB 10Gbps, USB 3.2 Gen2) with BC1.2 power charging</li> <li>2 x USB Type-C® downstream port (SuperSpeed USB 10Gbps, USB 3.2 Gen2) with power charging (15W)</li> </ul>
ADJUSTABILITY	Height adjustable (150 mm) Tilt (-5° to 21°) Swivel (-30° to 30°)
PBP / PIP	Yes
KEYBOARD, VIDEO AND MOUSE (KVM)	Yes
DAISY CHAIN AVAILABILITY	Yes
AUDIO OUTPUT	1 x Audio line-out1
BUILT-IN SPEAKER	2 x 9 W
DELL DISPLAY MANAGER COMPATIBILITY	Yes, Easy Arrange, Other key features

FEATURE SPECIFICATIONS - SERVICE / SUPPORT DETAILS	TECHNICAL SPECIFICATION 3-Year Advanced Exchange Service and Premium Panel Exchange
COLOR GAMUT	<ul style="list-style-type: none"> <li>sRGB 100%</li> <li>BT.709 100%</li> <li>DCI-P3 99%</li> <li>Display P3 99%</li> <li>1.07 billion colors (8bit + A-FRC)</li> <li>DCI-P3, Display P3, sRGB and BT.709: Delta E &lt; 2 (Average)</li> </ul>
HEIGHT WITH STAND (COMPRESSED ~ EXTENDED)	472.32 mm ~ 622.32 mm (18.60" ~ 24.50")
WIDTH WITH STAND	946.62 mm (37.27")
DEPTH WITH STAND	252.80 mm (9.95")
HEIGHT WITHOUT STAND	419.14 mm (16.50")
WIDTH WITHOUT STAND	946.62 mm (37.27")
DEPTH WITHOUT STAND	108.04 mm (4.25")
WEIGHT (PANEL ONLY - FOR VESA MOUNT)	8.35 kg (18.41 lb)
WEIGHT (WITH STAND ASSEMBLY AND CABLES)	12.22 kg (26.94 lb)
WEIGHT (WITH PACKAGING)	19.02 kg (41.93 lb)
SECURITY	Security lock slot (cable lock sold separately) Anti-theft stand lock slot (to lock stand to monitor using screw)
COMPLIANT STANDARDS	<ul style="list-style-type: none"> <li>ENERGY STAR® certified monitor</li> <li>EPEAT® registered where applicable. EPEAT registration varies by country. See <a href="http://www.epeat.net">www.epeat.net</a> for registration status by country.</li> <li>TCO Certified &amp; TCO Certified Edge</li> <li>RoHS Compliant</li> <li>BFR/PVC Free monitor (excluding external cables).</li> <li>Meets NFPA 99 leakage current requirements.</li> <li>Arsenic-Free glass and Mercury-Free for the panel only.</li> </ul>
FLAT PANEL MOUNT INTERFACE	VESA mounting holes (100 mm x 100 mm - behind attached VESA Cover)
TEMPERATURE RANGE	Operating: 0°C to 40°C (32°F to 104°F) Non-operating: -20°C to 60°C (-4°F to 140°F) - Storage and Shipping
HUMIDITY RANGE	Operating: 10% to 80% (non-condensing) Non-Operating: 5% to 90% (non-condensing) - Storage and Shipping
ALTITUDE	Operating: 5000 m (16404 ft) max Non-Operating: 12192 (40000 ft) max
VOLTAGE REQUIRED	100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 4.2 A (typical)
POWER CONSUMPTION NORMAL OPERATION	0.3 W (Off Mode)2 0.4 W (Standby Mode)2 1.8 W (Networked standby Mode)2 39.5 W (On Mode)2 380 W (Max)3 45 W (Pon)4 153.6 kWh (TEC)4
WHAT'S INCLUDED	Monitor, Stand Riser, Stand Base 1 x Power cable 1 x DisplayPort 1.4 cable - 1.8 m 1 x USB Type-A to USB Type-C Gen2 cable - 1 m 1 x HDMI cable - 1.8m 1 x Thunderbolt™ 4 active cable - 1.5 m Quick setup guide Safety, Environmental and Regulatory Information Factory calibration report

1 Headphone usage is not supported for the audio line out connector.

2 As defined in EU 2019/2021 and EU 2019/2013.

3 Max brightness and contrast setting with maximum power loading on all USB ports.

4 Pon: Power consumption of On mode as defined in Energy Star 8.0 version. TEC: Total energy consumption in kWh as defined in Energy Star 8.0 version.