



DELL ULTRASHARP
49 CURVED USB-C
HUB MONITOR
U4924DW

No gaps in productivity



**THE WORLD'S # 1
MONITOR COMPANY***

DELL Technologies

* Dell monitors are #1 Worldwide for 8 years (2014 to 2022)! Source: IDC
Worldwide Quarterly PC Monitor Tracker, Q3 2022

ULTRASHARP MONITOR

U4924DW

ULTRASHARP 49 CURVED USB-C HUB MONITOR – U4924DW TECHNICAL SPECIFICATION

DIAGONAL VIEWING SIZE	1,244.60 cm (49.00 inches)	HEIGHT WITH STAND (COMPRESSED ~ EXTENDED)	400.57 mm ~ 520.57 mm (15.77" ~ 20.49")
PRESET DISPLAY AREA (W X H)	1,198.08 mm x 336.96 mm (47.17" x 13.27")	WIDTH WITH STAND	1214.90 mm (47.83")
PANEL TYPE	IPS Black Technology	DEPTH WITH STAND	269.14 mm (10.60")
DISPLAY SCREEN COATING	Anti-Glare with 3H hardness	HEIGHT WITHOUT STAND	269.14 mm (10.60")
MAXIMUM PRESET RESOLUTION	5120 x 1440 at 60 Hz	WIDTH WITHOUT STAND	365.95 mm (14.41")
VIEWING ANGLE	178° vertical / 178° horizontal	DEPTH WITHOUT STAND	1214.90 mm (47.83")
PIXEL PITCH	0.234 mm x 0.234 mm		112.09 mm (4.41")
PIXEL PER INCH (PPI)	109	WEIGHT (PANEL ONLY - FOR VESA MOUNT)	12.15 kg (26.79 lb)
CONTRAST RATIO	2000 to 1 (typical)	WEIGHT (WITH STAND ASSEMBLY AND CABLES)	16.30 kg (35.93 lb)
ASPECT RATIO	32:9	WEIGHT (WITH PACKAGING)	27.73 kg (61.13 lb)
BACKLIGHT TECHNOLOGY	White LED Edgelight System	SECURITY COMPLIANT STANDARDS	Security lock slot2 (cable lock sold separately)
BRIGHTNESS	350 cd/m2 (typical)		• ENERGY STAR® certified Monitor.
COLOR GAMUT	100% sRGB, DCI-P3 98%, Display P3 98%, REC. 709 100% (Delta E<2), 1.07 billion colors		• EPEAT® registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration status by country.
RESPONSE TIME	5 ms gray to gray in Fast mode 8 ms gray to gray in Normal mode		• RoHS-compliant
HDR READY	No		• TCO Certified
CONNECTIVITY	• 1 x DisplayPort version 1.4 (HDCP2.2) • 2 x HDMI ports (HDCP2.2) (supports up to DQHD)	FLAT PANEL MOUNT INTERFACE	VESA mounting holes (200 mm x 100 mm (1) and 100 mm x 100 mm (2) are supported) - behind attached VESA Cover)
	5120 x 1440 60 Hz FRL as per specified in HDMI 2.1) 1 x USB Type-C upstream port (video and data) (Alternate mode with DisplayPort 1.4, Power Delivery up to 90W)	TEMPERATURE RANGE	Operating: 0°C to 40°C (32°F to 104°F) Non-operating: -20°C to 60°C (-4°F to 140°F)
	• 1 x USB-C upstream port (data only, 10 Gbps USB 3.2 Gen2)	HUMIDITY RANGE	Operating: 10% to 80% (non-condensing) Non-Operating: 5% to 90% (non-condensing)
	• 4 x SuperSpeed USB 10 Gbps (USB 3.2 Gen2) Type-A downstream port	ALTITUDE	Operating: 5000 m (16404 ft) max Non-Operating: 12192 (40000 ft) max
	• 2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen2) Type-C downstream port with charging capability at 15W (maximum)	VOLTAGE REQUIRED	100 VAC to 240 VAC / 50 Hz or 60 Hz + 3 Hz / 3.6 A (max) 0.3 W (Off Mode) ³
	• 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen2) Type-A with BC1.2 charging capability at 2 A (maximum)	POWER CONSUMPTION NORMAL OPERATION	0.3 W (Standby Mode) 45 W (On Mode) ³ 290 W (Max) ⁴
	• 1 x Audio line-out port		G
	• 1 x RJ45 2.5G port	ENERGY EFFICIENCY CLASS (A TO G SCALE)	
ADJUSTABILITY	Height adjustable (120 mm) Tilt (-5° to 21°) Swivel (-170° to 170°) Slant Adjust (-2° to 2°) Pivot (NA)	WHAT'S INCLUDED	Monitor, Stand Riser, Stand Base 1 x Power cable 1 x Type-C Gen 2 (C-C cable) - 1 m 1 x DisplayPort Cable (DP to DP) - 1.8 m 1 x (Type-A to Type-C) Gen 2 cable - 1 m 1 x HDMI cable (HDMI to HDMI) - 1.8 m Quick setup guide Safety, Environmental and Regulatory Information
PBP / PIP	PbP (Yes), PiP (Yes)		
KEYBOARD, VIDEO AND MOUSE (KVM)	Yes, KVM and Auto-KVM		
DAISY CHAIN AVAILABILITY	No		
AUDIO OUTPUT	1 x Audio line-out ¹		
BUILT-IN SPEAKER	2 X 9W		
DELL DISPLAY MANAGER COMPATIBILITY	Yes, Easy Arrange, Other key features		
SPECIFICATIONS - SERVICE / SUPPORT DETAILS	3-Year Advanced Exchange Service and Premium Panel Exchange		

1 Connect Speakers. Headphone Use is not supported for the audio line out connector.

2 Based on Kensington Security Slot™

3 As defined in EU 2019/2021 and EU 2019/2013.

4 Max brightness and contrast setting with maximum power loading on all USB ports.