



AORUS FI32U

TACTICAL
GAMING MONITOR

USER GUIDE

APPENDICES

Specifications

Item	Specifications
Panel Size	31.5-inch
Aspect Ratio	16:9
Resolution	3840 x 2160
LED Life	30000 hours (min.)
Pixel Pitch	0.181(H) x 0.181(V) mm
Brightness	350 (typ.)
Contrast Ratio	1000:1 (typ.)
Color Depth	1.073G
Active Display area	697.31(H) x 392.23(V)
Viewing Angle	178°(H) / 178°(V)
Frequency	144Hz
Input/Output Terminals	• 2x HDMI 2.1 • 1x DP1.4 • 1x Headphone • 1x Microphone • 1x USB-C (5V/3A, 9V/2A, 12V/1.5A, 15V/1A) • 2x USB 3.0 (downstream), support BC 1.2 charging (5V/1.5A) • 1x USB upstream • 1x Line-Out
Power Supply	100 to 240Vac at 50/60 Hz
Power Consumptions	• On: AC 120W (Max) • Standby: 0.5W • Off: 0.3W
Dimensions (W x H x D)	717.6 x 598.3 x 283 mm (with stand)
Weight	10.9 ±0.5 kg (Net)
Temperature Range (operation)	0°C to 40°C

Note: Specifications subject to change without notice.